

Collar Flange with Retaining Ring


Flange: ISO-F, compatible to ISO-K Flanges (DIN 28404) Leak rate: 1×10^{-9} mbar \cdot I/s Surface: Steel, nickel plated | Stainless Steel



Artikelnummer	Material	DN	А	В	С	D	E
063ÜF/A	Steel	DN 63	130.0	110.0	12	9	95.5
063ÜF/B	Stainless Steel (1.4301)	DN 63	130.0	110.0	12	9	95.5
100ÜF/A	Steel	DN 100	165.0	145.0	12	9	130.5
100ÜF/B	Stainless Steel (1.4301)	DN 100	165.0	145.0	12	9	130.5
160ÜF/A	Steel	DN 160	225.0	200.0	16	11	180.7
160ÜF/B	Stainless Steel (1.4301)	DN 160	225.0	200.0	16	11	180.7
200ÜF/A	Steel	DN 200	285.0	260.0	16	11	240.7
200ÜF/B	Stainless Steel (1.4301)	DN 200	285.0	260.0	16	11	240.7
250ÜF/A	Steel	DN 250	335.0	310.0	16	11	290.7
250ÜF/B	Stainless Steel (1.4301)	DN 250	335.0	310.0	16	11	290.7
320ÜF/A	Steel	DN 320	510.0	480.0	20	13.5	370.8
400ÜF/A	Steel	DN 400	510.0	480.0	20	13.5	450.8
500ÜF/A	Steel	DN 500	610.0	580.0	20	13.5	550.8
630ÜF/A	Steel	DN 630	750.0	720.0	24	13.5	691



Datasheet



this product is compliant with both REACH and RoHS regulations

www.wissel-vakuum.de